

Pasture Horse Feeder Roof Kit Assembly Instructions

(PHFHRKIT)



Roof Kit Parts:

- a. Roof Frame
- b. L-Brackets (quantity 4)
- c. Ground Stake with chain (quantity 4)
- d. Roof Support legs (quantity 4)
- e. Tin 95# (Quantity 3)
- f. Screws and Nuts included

Tools needed:

2 - 9/16" Wrenches (not included)

Step 1: Remove the nut from the leg brace on the Pasture Feeder and install the L-Bracket to the bolt and re-attach nut. Note: 'L' bend should be facing outward See Fig. 1.

Step 2: Drive the stake into the ground through the hole on the L-Bracket. Repeat for remaining 3 L-brackets.

Step 3: Remove clamps from all Roof Support Legs. There are 2 types of clamps for each side of the support system - round used on top side of the feeder and square used for bottom side of the feeder.

Step 4: Cup the round clamp on the top side of the feeder and tighten to the Roof Support Leg. (See Fig. 2a) Repeat on remaining 3 corners.

Step 5: Cup the square clamp on the bottom side of the feeder. (See Fig. 2b) Repeat on remaining 3 corners.

Step 6: Remove bolts out of the top of the four (4) Roof Support Legs and align with the tabs on the roof frame and fasten with bolts.

Step 7: Lay one piece of Tin on the roof frame and fasten to the frame with tin screws. Repeat with other two pieces.



Figure 1 - L-Bracket



Figure 2a - Round Clamp



Figure 2b - Square Clamp



WARNING - TIP OVER HAZARD

Do not install this product without installing leg braces and anchors first.